



MW2050 series slip rings

MW2050 series is large current slip ring with bore diameter 50mm. The through bore slip ring can be used for shaft installation or through gas-liquid catheter. This series slip ring can be with rated current 20A/30A/50A to over 100A.



Part# Explanation



Part# List

Mw2050 Series slip ring part# list																
Part#	50A	100A	150A	200A	300A	500A	length (mm)	Part#	50A	100A	150A	200A	300A	500A	Signal ring (Thermocouple)	Length (mm)
MW2050-P0160	1	0	0	0	0	0	59.6	MW2050-P0160-S06	1	0	0	0	0	0	6	82.4
MW2050-P01100	0	1	0	0	0	0	59.6	MW2050-P01100-S06	0	1	0	0	0	0	6	82.4
MW2050-P01150	0	0	1	0	0	0	82.4	MW2050-P01150-S06	0	0	1	0	0	0	6	105.2
MW2050-P01200	0	0	0	1	0	0	82.4	MW2050-P01200-S06	0	0	0	1	0	0	6	105.2
MW2050-P01300	0	0	0	0	1	0	105.2	MW2050-P01300-S06	0	0	0	0	1	0	6	128
MW2050-P01500	0	0	0	0	0	1	155.8	MW2050-P01500-S06	0	0	0	0	0	1	6	178.6
MW2050-P0260	2	0	0	0	0	0	82.4	MW2050-P0260-S06	2	0	0	0	0	0	6	105.2
MW2050-P02100	0	2	0	0	0	0	82.4	MW2050-P02100-S06	0	2	0	0	0	0	6	105.2
MW2050-P02150	0	0	2	0	0	0	105.2	MW2050-P02150-S06	0	0	2	0	0	0	6	128
MW2050-P02200	0	0	0	2	0	0	128	MW2050-P02200S-06	0	0	0	2	0	0	6	155.8
MW2050-P02300	0	0	0	0	2	0	178.6	MW2050-P02300-S06	0	0	0	0	2	0	6	224.2
MW2050-P02500	0	0	0	0	0	2	274.8	MW2050-P02500-S06	0	0	0	0	0	2	6	320.4
MW2050-P0360	3	0	0	0	0	0	82.4	MW2050-P0360-S06	3	0	0	0	0	0	6	105.2
MW2050-P03100	0	3	0	0	0	0	105.2	MW2050-P03100-S06	0	3	0	0	0	0	6	128
MW2050-P03150	0	0	3	0	0	0	155.8	MW2050-P03150-S06	0	0	3	0	0	0	6	178.6
MW2050-P03200	0	0	0	3	0	0	178.6	MW2050-P03200-S06	0	0	0	3	0	0	6	224.2
MW2050-P03300	0	0	0	0	3	0	274.8	MW2050-P03300-S06	0	0	0	0	3	0	6	274.8
MW2050-P03500	0	0	0	0	0	3	414.6	MW2050-P03500-S06	0	0	0	0	0	3	6	414.6
MW2050-P0460	4	0	0	0	0	0	105.2	MW2050-P0460-S06	4	0	0	0	0	0	6	128
MW2050-P04100	0	4	0	0	0	0	128	MW2050-P04100-S06	0	4	0	0	0	0	6	155.8
MW2050-P04150	0	0	4	0	0	0	178.6	MW2050-P04150-S06	0	0	4	0	0	0	6	224.2
MW2050-P04200	0	0	0	4	0	0	224.2	MW2050-P04200-S06	0	0	0	4	0	0	6	274.8
MW2050-P04300	0	0	0	0	4	0	320.4	MW2050-P04300-S06	0	0	0	0	4	0	6	369
MW2050-P0660	6	0	0	0	0	0	128	MW2050-P0660-S06	6	0	0	0	0	0	6	155.8

MW2050-P06100	0	6	0	0	0	0	178.6	MW2050-P06100-S06	0	6	0	0	0	0	6	224.2
MW2050-P06150	0	0	6	0	0	0	274.8	MW2050-P06150-S06	0	0	6	0	0	0	6	274.8
MW2050-P06200	0	0	0	6	0	0	320.4	MW2050-P06200-S06	0	0	0	6	0	0	6	369

Note: 1. N channels 60A rings parallel can be used as 1 channel N * 60A current. For example: 2 rings 60A parallel could be used as 1 wires 120A
 2. Optional for adding signal wire, thermocouple signal wire and high temperature resistance, it can be customized on customer's request.
 Please contact customer service for more information.

Specification

Electrical Data		
Parameter	Value	
	Power	Signal
Rated Voltage	0~690VAC/VDC	0~240VAC/VDC
Insulation Resistance	≥1000MΩ/1000VDC	≥500MΩ/500VDC
Lead Wires	AWG12#/AWG8# /AWG12#parallel/AWG8parallel	AWG22#Teflon / Type K Thermocouple
Lead Length	Standard 300mm	
Dielectric Strength	500VAC@50Hz, 60s	
Electrical Noise	<0.01Ω	
Mechanical Data		
Parameter	Value	
Working Life	See Product Quality Level Table	
Rotating Speed	See Product Quality Level Table	
Working Temperature	-30°C~80°C	
Operating Humidity	0~85% RH	
Contact Material	See Product Quality Level Table	
Housing Material	aluminium alloy / PBT	
Torque	0.1N.m; +0.03N.m/6rings	
Protection Grade	IP51	

Product Quality Level Table

Products Level Code	Max Rotating Speed	Working Life	Contact Material
VC	100RPM	10 Million Revs	Precious Metal
VD	200RPM	30 Million Revs	Gold-plated

Options for custom slip ring

Note: Below special demands can be customized. According, the delivery date will be extended 3 to 15 days; also the cost will be increased 30% to 50%. Most of our basic parts are standard and modular, which can save the cost and lead time.

- ① Cable exit way and cable length can be customized for both rotor and stator.
- ② Because of the structure limitation, length/height/OD can be customized on your request.
- ③ Support current or signal up to 200 rings.
- ④ Aviation plug, terminal and heat-shrink tube are optional.
- ⑤ Hybrid slip ring for Yaskawa/Panasonic/Siemens servo control signal, power line and encoder line.
- ⑥ Support mixed high speed data transmission (including Ethernet, USB, RS232, RS485, Profibus, CanBUS, CANOPEN, DeviceNET, CC-LINK, ProfiNET, EtherCAT, etc.)
- ⑦ Can combine temperature control signal with thermocouple signal.
- ⑧ Special environment can be customized, such as quakeproof, high temperature, etc.
- ⑨ Hybrid Pneumatic/hydraulic and electric slip ring can be mixed.
- ⑩ High temperature can up to 500 degrees.
- ⑪ High pressure can up to 110KV
- ⑫ Rotating speed can up to 10000RPM
- ⑬ Maximum current can up to 5000 amperes.
- ⑭ Military grade
- ⑮ Optional for underwater IP65, IP68.
- ⑯ Optional for stainless steel housing

Technical support: technical@moflon.com