


# MK43(4 passages Pneumatic Rotary Union--Can combine electric wires)



MK43 series is 4 passages Pneumatic Rotary Union(Can combine electric wires), with connection size G3/8", compact size, light weight, low torque, Also optional for transmitting power line, signal line, industrial bus, control line, Electromagnetic valve, induction line, etc.; Standard installation is flange mounting.

Media Types: compressed Air/Gas, vacuum, etc.


MK43 (rotary union only for pneumatic) drawing (4 in 4 out, connection size G3/8")



## Part list

Model	Passages	Connection Size	Adaptive tube
MK43	4	G3/8"	10~12mm


MK43S-S12 drawing 4 in 4 out, connection size G3/8" + 12~36 wires x signal(2A)



## Part list

Model	Passages	Connection Size	Adaptive tube	Signal(2A)	L(mm)
MK43S-S12	4	G3/8"	10~12mm	12	21
MK43S-S18	4	G3/8"	10~12mm	18	28
MK43S-S24	4	G3/8"	10~12mm	24	38.6
MK43S-S36	4	G3/8"	10~12mm	36	52.3


## MK43S-S56 drawing 4 in 4 out, connection size G3/8"



### Part list

Model	Passages	Connection Size	Adaptive tube	Signal(2A)
MK43S-S56	4	G3/8"	10~12mm	56

## MK43-PXX-SXX drawing 4 in 4 out, connection size G3/8" + signal(5A)/10A



### Part list

Model	Passages	Connection Size	Adaptive tube	10A	Signal(5A)	L(mm)
MK21-P0610	4	G3/8"	10~12mm	6	0	45.2
MK21-S06	4	G3/8"	10~12mm	0	6	45.2
MK21-P1210	4	G3/8"	10~12mm	12	0	65.6
MK21-P0610-S06	4	G3/8"	10~12mm	6	6	65.6
MK21-S12	4	G3/8"	10~12mm	0	12	65.6
MK21-P1810	4	G3/8"	10~12mm	18	0	86
MK21-P0610-S12	4	G3/8"	10~12mm	6	12	86
MK21-P1210-S06	4	G3/8"	10~12mm	12	6	86
MK21-S18	4	G3/8"	10~12mm	0	18	86
MK21-S24	4	G3/8"	10~12mm	0	24	106.4
MK21-P0610-S18	4	G3/8"	10~12mm	6	18	106.4
MK21-S30	4	G3/8"	10~12mm	0	30	126.8
MK21-S36	4	G3/8"	10~12mm	0	36	150.2

Note:10A and signal(5A) can be freely combined, please contact customer service for details.

### Specifications

Rotary Union Specifications			Mechanical data	
Parameter	Value		Parameter	Value
Passage	4 in 4 out, G3/8"		Working life	Over 10 Million Revs
Max Pressure	1MPa(high pressure can be customized), Vacuum 0.01torr		Rated Rotating Speed	500RPM
Torque	Related to the connection size, please see the product selection table		Working Temperature	-30°C~80°C
Electrical Data			Operating Humidity	0~85% RH
Parameter	Value		Contact Material	Precious Metal
	Power	Signal	Housing Material	Aluminium Alloy
Rated Voltage	0~440VAC/VDC	0~440VAC/VDC	Protection Grade	IP51
Insulation Resistance	≥1000MΩ/500VDC	≥1000MΩ/500VDC		
Lead Wires	AWG16#Teflon/PVC	AWG22#Teflon/PVC		
Lead Length	Standard 300mm(adjustable on request)			
Dielectric Strength	500VAC@50Hz , 60s			
Electrical Noise	<0.01Ω			